

DOOR VIEWERS

SECURITY HARDWARE

DOOR VIEWERS



B02

- Solid brass door viewer
- Acrylic optical lens
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
B02	C26D		12 mm	—	160°	25
B03	C3, C26D	1 $\frac{3}{8}$ –2 $\frac{1}{4}$ (35–57)	14 mm	—	180°	25
B04	C3, C26D		16 mm	—	200°	10

IN (MM)



DV160



DV180, DV200

- Solid brass door viewer
- cULus 20 minute fire rating for labelled fire doors
- Polished glass and acrylic optical lenses
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV160	26, 26D	1 $\frac{3}{8}$ –2 (35–51)	12 mm	20 min	160°	25
DV180	26D, 19		14 mm	20 min	180°	25
DV200	26D	1 $\frac{3}{8}$ –2 $\frac{1}{4}$ (35–57)	14 mm	20 min	200°	10

IN (MM)



DV1012SRG



DV1012BRQ



DV1012BLQ

- Solid brass door viewer
- cULus 90 minute fire rating for labelled fire doors
- Polished glass and quartz lens
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV1012SRG	15, 19, 26D	1 $\frac{1}{16}$ –1 $\frac{1}{16}$ (17.5–27)	12 mm	90 min	160°	25
DV1012BRQ	26	1 $\frac{3}{8}$ –2 (35–51)	12 mm	90 min	160°	42
DV1012BLQ	19, 26	1 $\frac{3}{4}$ –2 $\frac{1}{4}$ (44.5–57)	12 mm	90 min	200°	25
DV1014BLQ	C15, C19, C26, 26D		14 mm	90 min	200°	25

IN (MM)

