




CAM LOCKS

SECURITY HARDWARE

Viro SOLID BRASS CAM LOCK




- Solid brass, fully threaded, pin tumbler cylinder
- Handed models supplied RH, LH available on special order
- Milled on one side to prevent rotation (single "D")
- 1012 and 1013 come with center plug position
- Universal use, easy to install on wood or metal cabinet and mailbox
- Supplied with 4 prong steel washer, securing nut, cam screw and 2 keys
- Custom keyed systems available
- Supplied with cam, please specify cam model
- Finish: natural brass (C3) or nickel plated (C15)

1053	KD	C15
MODEL	KEYING	FINISH


Wide variety of padlocks and specialty locks available – please contact to order or visit www.viro.it for details



301KB for 1012 & 1052 cam locks
302KB for 1003, 1004, 1005, 1013, 1053, 1054, 1055 & 1056 cam locks
 All key blanks are nickel plated brass



CAM dimensions are in millimetres.



MODEL	DEGREE OF TURN	PLUG POSITION	KEY REMOVAL	KEYWAY	HANDING	øA	øB	C	D	E	/BOX
1003	90°	Vertically offset	Locked	013	Right hand	15/16 (24.0)	1 9/32 (32.8)	1 3/16 (21.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1004	90°	Vertically offset	Locked	013	Right hand	15/16 (24.0)	1 9/32 (32.8)	1 1/32 (26.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1005	90°	Vertically offset	Locked	013	Right hand	15/16 (24.0)	1 9/32 (32.8)	1 7/32 (31.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1012	90°	Centered	Locked or Unlocked	011	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 1/16 (17.5)	2 5/32 (20.0)	2 3/32 (18.3)	12
1013	90°	Centered	Locked or Unlocked	013	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 3/16 (21.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1052	180°	Vertically offset	Locked	011	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 1/16 (17.5)	2 5/32 (20.0)	2 3/32 (18.3)	12
1053	180°	Vertically offset	Locked	013	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 3/16 (21.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1054	180°	Vertically offset	Locked	013	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 1/32 (26.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1055	180°	Vertically offset	Locked	013	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 7/32 (31.0)	2 5/32 (20.0)	2 3/32 (18.3)	12
1056	180°	Vertically offset	Locked	013	Non-handed*	15/16 (24.0)	1 9/32 (32.8)	1 3/8 (35.0)	2 5/32 (20.0)	2 3/32 (18.3)	12

IN (MM) (*) CONFIGURED FOR RIGHT-HAND USE, CAN BE CONVERTED TO LEFT-HAND