

DOOR VIEWERS

SECURITY HARDWARE

DOOR VIEWERS



B02

- Solid brass door viewer
- Acrylic optical lens
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
B02	C3, C26D		12mm	—	160°	25
B03	C3, C26D	1 ³ / ₈ – 2 ¹ / ₄ (35–57)	14mm	—	180°	25
B04	C3, C26D		16mm	—	200°	10

IN (MM)



DV160



DV180, DV200

- Solid brass door viewer
- cULus 20 minute fire rating for labelled fire doors
- Polished glass and acrylic optical lenses
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV160	3, 26, 26D	1 ³ / ₈ – 2 (35–51)	12mm	20 min	160°	25
DV180	26D		14mm	20 min	180°	25
DV200	26D	1 ³ / ₈ – 2 ¹ / ₄ (35–57)	14mm	20 min	200°	10

IN (MM)



DV1012BRQ



DV1012BLQ

- Solid brass door viewer
- cULus 90 minute fire rating for labelled fire doors
- Polished glass and quartz lens
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV1012BRQ	26	1 ³ / ₈ – 2 (35–51)	12mm	90 min	160°	42
DV1012BLQ	19, 26	1 ³ / ₈ – 2 ¹ / ₄ (35–57)	12mm	90 min	200°	25
DV1014BLQ	15, 19, 26D		14mm	90 min	200°	25

IN (MM)



DV1016LG

- Solid brass door viewer
- UL 20 minute fire rating
- Polished optical glass lenses
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV1016LG	26D	1 ³ / ₈ – 2 ¹ / ₄ (35–57)	16mm	20 min	180°	25

IN (MM)