



**BHMA**  
CERTIFIED



- Certifications**
- Certified ANSI/BHMA A156.13, Series 1000, Grade 1
  - cULus listed, 3hr fire-rating
  - UL10C Positive Pressure Rated
  - Levers meet ADA (ANSI 117.1) requirements
  - 5 Year limited warranty

- Door Thickness**
- 1¾" (44.5 mm)
  - 2-2¼" (51-57 mm) – available

**Handing** • Handed, field reversible

**Backset** • 2¾" (70 mm)

- Spring Latch**
- Brass, anti-friction
  - ¾" (19 mm) throw
  - Auxiliary deadlocking latch

**Deadbolt**

- Solid bolt, 2 security pins
- 1" (25.4 mm) throw

**Faceplate**

- 1¼ x 8" (32 x 203 mm), square corners
- Adjusts for bevelled doors up to ⅛" (3 mm)

**Strike** • ASA T-type strike and dust-box

**Cylinder**

- 6 pin mortise cylinder
- Schlage "C" with 2 keys

*Other keyways and keying options available.*

**Escutcheon Trim**

- Brass escutcheon with indicator
- E-Regular 2x8¼x½" (50x205x12.7 mm)

**Chassis**

- Escutcheon: exposed mounting screws
- Single action egress

**Functions** • 42I – Privacy, deadbolt with occupancy indicator

**Lever Styles** A–Apollo, R–Circa, C–Cornell, D–Dartmouth, G–Glasgow, L–Linea, S–Stanford, F–The Flat T–Strata

**Knob Styles** K–Kent

**Finish** 15–Satin nickel, 26D–Satin chrome

*Other finishes available by special order*

DM	42I	L	-	E	S	26D
SERIES	FUNCTION <sup>1</sup>	HAND		TRIM <sup>1</sup>	STYLE	FINISH

L : LEFT HAND R : RIGHT HAND (1) 42I FUNCTION ONLY AVAILABLE WITH E TRIM


## SELECTION GUIDE

SERIES	FUNCTION	FINISH	/CASE
DM42I	42I Privacy indicator with cylinder ➔	15, 26D	6


OTHER FINISHES AND FUNCTIONS AVAILABLE, MINIMUM ORDER QUANTITIES AND/OR ADDITIONAL DELIVERY TIMES MAY BE REQUIRED  
 ➔ KEYED FUNCTION; FULL KEYING SERVICES AVAILABLE

### LEVERS & KNOBS


A-Apollo




C-Cornell




D-Dartmouth




F-The Flat




G-Glasgow




L-Linea




R-Circa




S-Stanford



T-Strata



K-Kent



STYLE	A	B	C <sup>1</sup>
A-Apollo	3 <sup>1</sup> / <sub>16</sub> (78)	4 <sup>5</sup> / <sub>8</sub> (116)	2 <sup>1</sup> / <sub>16</sub> (53)
C-Cornell	2 <sup>7</sup> / <sub>8</sub> (73)	5 <sup>5</sup> / <sub>16</sub> (134)	5/ <sub>8</sub> (16)
D-Dartmouth	2 <sup>7</sup> / <sub>16</sub> (61.5)	5 <sup>7</sup> / <sub>8</sub> (149)	1 <sup>1</sup> / <sub>16</sub> (17)
F-The Flat	2 <sup>7</sup> / <sub>8</sub> (73)	2 <sup>1</sup> / <sub>2</sub> (139.7)	2 <sup>3</sup> / <sub>16</sub> (55.5)
G-Glasgow	2 <sup>7</sup> / <sub>8</sub> (73)	5 <sup>1</sup> / <sub>16</sub> (128)	2 <sup>1</sup> / <sub>16</sub> (52)

STYLE	A	B	C <sup>1</sup>
L-Linea	2 <sup>13</sup> / <sub>16</sub> (71.4)	5 (127)	1 <sup>15</sup> / <sub>16</sub> (48.4)
R-Circa	2 <sup>9</sup> / <sub>16</sub> (65.5)	2 <sup>1</sup> / <sub>2</sub> (139.7)	1 <sup>7</sup> / <sub>8</sub> (47)
S-Stanford	2 <sup>9</sup> / <sub>16</sub> (65.5)	5 <sup>1</sup> / <sub>16</sub> (128)	9/ <sub>16</sub> (14)
T-Strata	3 <sup>1</sup> / <sub>8</sub> (79.4)	5 <sup>1</sup> / <sub>8</sub> (130.2)	2 <sup>1</sup> / <sub>8</sub> (54)
K-Kent	2 <sup>7</sup> / <sub>16</sub> (61.5)	ø 2 (50.8)	—

IN (MM) (1) ALL ROSES AND ESCUTCHEONS ARE 1/2(12.7) THICK





## PARTS & ACCESSORIES



### DM45X-PS

Replacement strike for 1 $\frac{3}{4}$  (45) thick door.  
(Functions 42, 45, 56, 84)



### DM00X-PKDT225

Installation kit for 2–2 $\frac{1}{4}$  (51–57) thick doors.

- Includes extended thumb-turn, spindle, springs, strike and mounting hardware for sectional or escutcheon trim
- Mortise cylinder NOT INCLUDED  
*Please contact for details*



### DM00X-PCAM

Replacement mortise cylinder cam, with screws

NOTE: OTHER CYLINDERS MAY REQUIRE A DIFFERENT CAM. PLEASE CONTACT IF USING A DIFFERENT CYLINDER. OTHER CAMS SOLD SEPARATELY.



### DM00X-PSCYL

- 1 $\frac{1}{4}$  (28.6) 5-pin (drilled 6) brass mortise cylinder; Schlage "C" with 2 keys
- For sectional installations on 1 $\frac{3}{4}$  (45) thick doors
- Includes DM00X-PCAM
- Finish: 15, 19, 26D

### DM00X-PECYL

- 1 $\frac{1}{4}$  (31.8) 5-pin (drilled 6) brass mortise cylinder; Schlage "C" with 2 keys
- For escutcheon installations on 1 $\frac{3}{4}$  (45) thick doors
- Includes DM00X-PCAM
- Finish: 15, 19, 26D

