

# HINGE PIN STOPS


GENERAL HARDWARE

## HINGE PIN STOPS

805, 3506



805



### 805

- For use on hinged doors
- Adjustable door opening angle
- Fits 1/4" (6 mm) diameter hinge pin

### 3506

- For use on hinged doors
- Adjustable door opening angle
- Removable nylon bushing
- Fits 1/4" (6 mm) or 5/16" (7.5 mm) diameter hinge pins



3506C15

MODEL	FINISH	A	B	C	D	øE	øF	/BOX
805	Brass plated	1 5/8 (41.3)	1 5/8 (41.3)	1 1/8 (28.6)	1 5/8 (41.5)	1/2 (13)	1/4 (6.4)	25
3506	C3, C11P, C15, C15A, C26D	1 5/8 (41.3)	2 (50.8)	1 1/8 (28.6)	1 15/16 (49.2)	9/16 (14.7)	1/4 OR 5/16* (6.4 OR 7.5)	25


IN (MM) (\*) REMOVE BUSHING FOR LARGER DIAMETER

## HINGE PIN STOP – PIVOTING SHOE

3507



3507C15



- For use on hinged doors
- Adjustable door opening angle
- Removable nylon bushing
- Fits 1/4" (6 mm) or 5/16" (7.5 mm) diameter hinge pins
- Zinc die-cast body
- Self-pivoting shoe

MODEL	FINISH	A	B	C	D	øE	øF	/BOX
3507	C3, C11P, C15, C15A, C26D	1 7/16 (36.5)	1 7/8 (47.6)	1 1/8 (28.6)	2 (50.8)	1/2 (13)	1/4 OR 5/16* (6.4 OR 7.5)	50


IN (MM) (\*) REMOVE BUSHING FOR LARGER DIAMETER

## HINGE PIN STOP

3508



3508C15A



- For use on hinged doors
- Adjustable door opening angle
- Zinc die-cast body
- Removable nylon bushing
- Fits 1/4" (6 mm) or 5/16" (7.5 mm) diameter hinge pins

MODEL	FINISH	A	B	C	D	øE	øF	/BOX
3508	C15A, C26D	1 7/16 (36.5)	1 7/8 (47.6)	1 1/4 (31.8)	1 15/16 (49.2)	1/2 (13)	1/4 OR 5/16* (6.4 OR 7.5)	50

IN (MM) (\*) REMOVE BUSHING FOR LARGER DIAMETER