


MAIL SLOTS

GENERAL HARDWARE

DraftGuard INSULATED MAIL SLOT

46500



	REGULAR	WITH EXTENSION*
(A) Front	11 ⁷ / ₈ x 2 ³ / ₄ (302 x 70)	—
(B) Slot Size	10 x 1 ¹ / ₂ (254 x 38)	—
(C) Door cut-out	11 ¹ / ₈ x 2 (280 x 51)	11 ¹ / ₄ x 2 (286 x 51)

IN (MM) (*) EXTENSION MUST BE USED WITH DOORS OVER 1³/₄ IN (44.5 MM) THICK AND SLOT MUST BE CUT WITH FINE-TOOTH SAW.

- Self-closing interior and exterior anodized aluminum flaps
- Fully enclosed tough plastic housing
- Telescopic housing for doors up to 1³/₄" (44.5 mm) thick
- Up to 4¹/₄" (108 mm) with extension (sold separately)
- Soft rubber weather exterior seal
- Insulating gaskets in all critical areas



#465001..... Aluminum

#465005..... Dark Bronze

#465006..... Brass

#465007..... White



#465000..... Slot extension.
For doors 1³/₄–4¹/₄" (44.5–108 mm)

#465000L..... Screw pack for slot extension

#465000R..... Replacement screws for mail slot

