



NOTES:

1. APPLICABLE TO COMMERCIAL LOCKS (WITH ANSI/ASA STRIKE):
 - GRADE 2: EM, EL
 - LOCKS WITH 64 mm CENTER-TO-CENTER DISTANCE BETWEEN REMOVABLE POSTS
2. DRAWING DEPICTS WOOD OR METAL FRAME AND WOOD OR COMPOSITE DOOR WITH:
 - 2-3/4" BACKSET
 - 1-3/4" DOOR THICKNESS
3. REFERENCE:
 - ANSI A156.115W
 - DOOR PREP 161
4. IT IS RECOMMENDED THAT PHYSICAL HARDWARE BE ORDERED AND VERIFIED BEFORE STARTING THE PRODUCTION OF DOORS.

1. DRAWING DEPICTS 2 3/4" BACKSET. IF 2 3/8" OR OTHER BACKSET IS DESIRED, CHANGE THE BACKSET TO THE DESIRED ONE
2. CONFIRM BOLT CENTER-TO-CENTER DISTANCE WITH LOCK MODEL (REFER TO LOCKSET INSTALLATION INSTRUCTIONS)
3. DRAWING DEPICTS 1 3/4" DOOR THICKNESS, FOR OTHER DOOR THICKNESS POSITION THE LATCH CENTER AT HALF OF THE DOOR THICKNESS AND ADJUST STRIKE POSITION ACCORDINGLY
4. DO NOT DRILL THE POST HOLES WHEN LOCK IS USED WITHOUT POSTS
5. CONFIRM LATCH FACEPLATE SIZE. DRAWING DEPICTS STANDARD COMMERCIAL LOCK LATCH FACEPLATE SIZE FOR 2 3/4" BACKSET. THE FACEPLATE OF THE 2 3/8" BACKSET LATCH MAY BE 1" WIDE X 2 1/4" HEIGHT

DIMENSIONS INCHES
MM

DO NOT SCALE DIMENSIONS ON DRAWING

TOLERANCES			CANAROPA		
Ø.XX	Ø.XXX	DEGREES	DRAWN	DATE	TITLE
± 0.03	± 0.010	± 0.5	CC	19-OCT-17	DOOR & FRAME PREP FOR COMMERCIAL CYLINDRICAL LOCKS FOR 1 3/4" THICK WOOD/COMPOSITE DOORS AND 2 3/4" BACKSET 64 mm C-TO-C
MATERIAL N/A			APPR'D	DATE 19-OCT-17	
FINISH N/A			APPR'D REVISION	DATE	SCALE 1:1
					DWG NO CAN-DP-ANSI-A156.115W-64mm