



- NOTES:
1. APPLICABLE TO COMMERCIAL LOCKS (WITH ANSI/ASA STRIKE):
 - GRADE 1: GX1L, G1L, F1H, F1C, F1S
 - GRADE 2: FH, FC, FS, T2
 - LOCKS WITH 70 mm CENTER-TO-CENTER DISTANCE BETWEEN POSTS
 2. DRAWING DEPICTS WOOD OR METAL FRAME AND WOOD OR COMPOSITE DOOR WITH:
 - 2-3/4" BACKSET
 - 1-3/4" DOOR THICKNESS
 3. REFERENCE:
 - ANSI A156.115W
 - DOOR PREP 161

- 1 DRAWING DEPICTS 2 3/4" BACKSET. IF 2 1/4" OR OTHER BACKSET IS DESIRED, CHANGE THE BACKSET TO THE DESIRED ONE
- 2 CONFIRM BOLT CENTER-TO-CENTER DISTANCE WITH LOCK MODEL (REFER TO LOCKSET INSTALLATION INSTRUCTIONS)
- 3 DRAWING DEPICTS 1 3/4" DOOR THICKNESS. FOR OTHER DOOR THICKNESS POSITION THE LATCH CENTER AT HALF OF THE DOOR THICKNESS AND ADJUST STRIKE POSITION ACCORDINGLY
- 4 DO NOT DRILL THE POST HOLES WHEN LOCK IS USED WITHOUT POSTS
- 5 CONFIRM LATCH FACEPLATE SIZE. DRAWING DEPICTS STANDARD COMMERCIAL LOCK LATCH FACEPLATE SIZE FOR 2 3/4" BACKSET. THE FACEPLATE OF THE 2 3/4" BACKSET LATCH MAY BE 1" WIDE X 2 1/4" HEIGHT

Document provided as-is, manufacturer reserves the right to make technical changes without prior notice.

DIMENSIONS INCHES / MM

DO NOT SCALE DIMENSIONS ON DRAWING

TOLERANCES			CANAROPA			
0.XX	0.XXX	DEGREES	DRAWN	DATE	TITLE	
± 0.03	± 0.010	± 0.5	CC	13-JAN-16	DOOR & FRAME PREP FOR COMMERCIAL CYLINDRICAL LOCKS FOR 1 3/4" THICK WOOD DOORS AND 2 3/4" BACKSET	
MATERIAL			APPR'D	DATE	SCALE 1:1	
N/A				13-JAN-16	DWG NO	
FINISH			APPR'D REVISION	DATE	REV-	
N/A					CAN-OP-ANSI-A156.115W-MOD	