



Camden Door Controls is an industry-leading provider of innovative, high quality and competitively priced door activation, control and locking products for any access control or automatic door application. Camden Door Controls bring an unsurpassed combination of product quality, performance and value to every access control and automatic door project.

www.camdencontrols.com




ELECTRIC STRIKES



BHMA
G1
UL US LISTED
SECURITY UL LISTED

CX-ED1579L
ALL-IN-ONE, FIRE RATED
ELECTRIC STRIKE





BHMA
G1
UL US LISTED
SECURITY UL LISTED

CX-ED1420
UNIVERSAL, FIRE RATED
ELECTRIC STRIKE




BHMA
G1
SECURITY UL LISTED

CX-ED1079
LOW-PROFILE UNIVERSAL
ELECTRIC STRIKE



BHMA
G1
SECURITY UL LISTED

CX-ED1379
NARROW STILE
ELECTRIC STRIKE





BHMA
G1
UL US LISTED
SECURITY UL LISTED

CX-ED1410
UNIVERSAL, FIRE RATED
ELECTRIC STRIKE



BHMA
G2
SECURITY UL LISTED


CX-ED2079
LOW-PROFILE UNIVERSAL
ELECTRIC STRIKE



CX-EPD1289L
SURFACE MOUNTED,
FIRE RATED, RIM
ELECTRIC STRIKE

Grade 1 surface mount RIM strike, with latch monitoring, offers a 'Universal' strike design

BHMA G1 UL US LISTED SECURITY UL LISTED



FOR RIM
EXIT DEVICES



ELECTROMAGNETIC LOCKS



SECURITY
UL LISTED

CX-DE1200 « Exit Watch »
DELAYED EGRESS MAGNETIC LOCK
(1200 LBS)

- Nuisance delay period
- Voice and LED count-down timer
- Vandal resistant proximity trigger sensor
- Auto sensing power input with polarity protection
- Auto/manual start-up on power restore
- Anti-Pass back/Auto Re-Lock



SECURITY
UL LISTED

CX-915-12TDS
SINGLE DOOR MAGNETIC LOCK
(1200 LBS)

- Surface mount model
- Adjustable timer
- Door status switch
- Lock sensor/relay
- LED indicator
- Compatible with all access/egress systems
- Field selectable 12/24 VDC operation
- Weather and vandal resistant
- On board power surge protection



ACCESS CONTROL KITS



CX-WC13AXSM
BARRIER FREE RESTROOM CONTROL:

- Logic control board
- Narrow "Push to Open" and "Push to Lock" push plates with LED mounting box and sign
- Push plate with LED mounting box and sign
- Magnetic Contact, surface mounted

*Mounting boxes are surface mounted.
Power supply and electric strike are not included.*



CX-WEC10K2
EMERGENCY CALL FOR UNIVERSAL RESTROOMS:

- Double gang, emergency call button
- Single gang dome light with alarm
- Solid white sign (English / French)

Mounting boxes are not included.

ACCESS CONTROL COMPONENTS



CM-30C
SQUARE ILLUMINATED EXIT SWITCH:

- High visibility 2" (51 mm) square button
- Single gang with stainless steel faceplate
- Bright LED provides clarity and longevity
- Variety of bilingual labels



KEY SWITCHES

CM-1105..... SPST, N/C
CM-1120..... SPDT, Momentary N/O and N/C
CM-170/24..... SPDT, Momentary

MORTISE CYLINDER
SOLD SEPARATELY



CM-400
PUSH BUTTON STAINLESS STEEL FACEPLATE:

- 1 5/8" (40 mm) diameter button
- Vandal resistant free-spinning button
- Single gang stainless steel face plate
- Available in English or French



CM-701U
BLUE PULL STATION

INCLUDED LABELS



CM-AF500
LED ANNUNCIATORS:

- Bright LEDs for high visibility, even in daylight
- Text/graphics are not legible when not illuminated
- Vandal and weather resistant construction
- Single gang stainless steel face plate

READERS & KEYPADS



CV-110SPK
SLIM LINE CARD READER & KEYPAD
125KHz Reader



CM-110SK
SLIM LINE KEYPAD

MAGNETIC CONTACT



MAGNETIC CONTACT
CX-MDH..... SPST, Recessed, White



MAGNETIC CONTACT
CX-MDA..... SPST, White

PUSH PLATES



CM-45/4 **CM-45/4F**

PUSH PLATES
4 1/2 x 4 1/2 in (114.3 x 114.3 mm)
CONCEALED MOUNTING

CM-45/4..... English
CM-45/4F..... French
CM-45/2..... Signage
CM-45/K2..... Wireless



CM-60/4 **CM-60/F**

ROUND PUSH PLATES
6 in Round (152.4 x 152.4 mm)
CONCEALED MOUNTING

CM-60/4..... English
CM-60/4F..... French
Mounting boxes not included.




CM-45/2 **CM-45/K2**



CM-40/2

CM-40/2
4.5in Round (114.3mm)
CONCEALED MOUNTING
Mounting boxes not included.

PUSH PLATE SWITCHES



**CM-7536/1
COLUMN PUSH PLATE SWITCH**

- Aluminum push plate 36x 6in (mm)
- Surface mounted
- OBC, NBC, & CSA compliant
- Also available in dark bronze

POWER SUPPLY



**CX-PS150UL
POWER SUPPLY**

- 12/24 VDC selectable 1.7 Amp output
- AC and DC power and status indicators
- UL 294 and ULC S533
- 120 VAC power input
- Built in battery charger (500mA)

MOUNTING BOXES



CM-34BL

SURFACE MOUNTED, SINGLE GANG

- Standard depth
- 2¾x4½x1¾in (70x114x44.5mm)
- Single gang
- Provision for wireless
- Flame/impact resistant black ABS



CM-43LP

SURFACE MOUNTED, PUSH PLATE

- Shallow depth
- 5 x 5 x 1¾in (127 x 127 x 35 mm)
- Double gang
- Flame/impact resistant black ABS
- For use with CM-45/46 push plate



CM-43CBL

SURFACE MOUNTED, WIRELESS

- Standard depth
- 4½x4½x2in (114x114x51mm)
- Double gang
- Provision for wireless
- Flame/impact resistant black ABS



CM-43CBLA

SURFACE MOUNTED, HANDS FREE

- Standard depth
- 4½x4½x2in (114x114x51mm)
- Double gang
- Provision for wireless
- Flame/impact resistant black ABS
- For CM-324/325/330 hands free switches



CM-69S

ROUND MOUNTING BOXES - SURFACE

- Standard depth
- 6.25in x 6.25in x 2in (158.75x158.75x50.8mm)
- Provision for wireless
- Flame/impact resistant black ABS

LOGIC RELAYS



CX-12 PLUS

DOOR INTERFACE RELAY

Designed for easy interconnection of automatic doors with access control, time control, telephone entry and fire alarm systems.



CX-33

ADVANCED LOGIC RELAY

Ideal for most automatic door applications, as well as air lock and other security applications.



Looking For More Camden Products?

OFFICIAL DISTRIBUTOR.

All Camden Door Control products are available through Canaropa.

Please contact your local Canaropa sales representative to order – special orders may require additional delivery time and/or minimum order quantities.

Learn more about Camden Door Control and their products at:
www.camdencontrols.com



CM-RX-90

**V2 KINETIC/LAZERPOINT
ADVANCED 1 RELAY RECEIVER**



CM-RX-91

**BASIC SINGLE RELAY
RECEIVER**



CM-RX-92

**FULL FUNCTION DUAL
RELAY RECEIVER**



CM-TX-9

**WALL SWITCH
TRANSMITTER**

